Safety Data Sheet



Issue Date: 17-Sept-2008 Revision Date: 21-Apr-2022 Version 1

1. IDENTIFICATION

Product Identifier

Product Name ODP-340 Fuel/Oil Leak Test Powder

Other means of identification

SDS # AGC-236
Product Code ODP-340
UN/ID No None

 Other Information
 Package type: Poly Bottles

 Recommended use of the chemical and restrictions on use

 Recommended Use
 Fuel/Oil Leak Testing Powder

Details of the supplier of the safety data sheet

Manufacturer Address AMERICAN GAS & CHEMICAL COMPANY, LTD

220 Pegasus Avenue Northvale NJ 07647

Emergency Telephone Number

Company Phone Number Phone: 201-767-7300 Fax: 201-767-1741 Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Pink Powder Physical State Powder Odor Slight odor

Classification

Under normal conditions of use, this product is not expected to create any unusual hazard. This product is not flammable, not reactive, not explosive has no flash point, and poses no special hazards in the presence of fire.

Hazards Not Otherwise Classified (HNOC)

None

Signal Word Warning

Hazard Statements

May cause eye irritation May cause mild skin irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

<u>Precautionary Statements - Response</u>

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing if eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Talc	14807-96-6	99

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye ContactAcute: If splashed into the eyes, flush with clear water for 15 minutes or until irritation

subsides. May cause mechanical irritation of the eyes. If irritation persists, call physician.

Chronic: Repeated exposure may cause conjunctive inflammation.

Skin contactAcute: Direct contact may cause dryness or mild irritation if an allergic predisposition exists.

Chronic: Prolonged contact may cause dryness of skin or mild irritation if an allergic

predisposition exists.

Ingestion Acute: This material is considered to be harmless and inert when ingested.

Chronic: Repeated ingestion in large doses of talc for 10 & 13 consecutive days by mice

and rabbits revealed negative teratogenic and carcinogenic results.

Inhalation Acute: Exposure to a large concentration of air-borne dust of this material may cause

mechanical irritation of the mucous membranes and respiratory tract.

Chronic: Repeated and prolonged exposure to large amount of talc dust might induce a mild pneumoconiosis. This is caused by lung overload exposure, a non specific particle

effect, rather than a specific intrinsic fibrogenic activity of talc.

Most important symptoms and effects

Symptoms High concentrations are irritating to the respiratory tract, may cause headaches and

dizziness. Prolonged or repeated skin contact tends to remove skin oils possibly leading to

irritation and dermatitis. Contact may cause eye irritation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

All extinguishing media can be used.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

This product is not flammable, combustible or explosive. No hazardous thermal decomposition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool exposed containers with water spray. Avoid breathing vapor or fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid airborne dust generation. If the generation of dust is likely, personal protective

equipment should be worn in compliance with national legislation.

For Emergency Responders Follow applicable OSHA regulations (29 CFR 1910.120).

Environmental Precautions No special requirements. Contain spillage and clean up as indicated below.

Methods and material for containment and cleaning up

Methods for Containment Dry product should be cleaned with a shovel or a vacuum cleaner while wearing personal

protective equipment in compliance with national legislation. Talc is not considered a hazardous waste as defined by the US EPA RCRA (40 CFR 261) regulations. Observe all applicable federal, state and local regulations when handling, storing or disposing of this

substance.

Methods for Clean-Up Sweep up absorbed material and shovel into suitable containers for disposal. Discard any

product, residue, disposable container or liner in full compliance with federal, state, and

local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Avoid airborne dust generation. Provide appropriate exhaust ventilation at places where

airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory

protective equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep

containers closed and plainly labeled when not in use.

Incompatible Materials None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc	TWA: 2 mg/m ³ particulate matter	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%	respirable dust <1% Crystalline	TWA: 2 mg/m ³ containing no
	crystalline silica, respirable	silica, containing no Asbestos	Asbestos and <1% Quartz
	fraction	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more, use Quartz limit	

Appropriate engineering controls

Engineering Controls Minimize airborne dust generation. Use process enclosures, local exhaust ventilation or

other engineering controls to keep airborne levels below specified exposure limits.

Remarks • Method

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use safety goggles or face shield with side shields in circumstances where there is a risk of

dust generation which could lead to mechanical irritation of the eyes.

Skin and Body Protection No specific requirements. Protective gloves are not necessary but recommended for those

prone to skin irritation or dryness.

Respiratory Protection In case of overexposure to airborne dust concentrations, wear respiratory protective

equipment that complies with the requirements of national legislation.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical StatePowderAppearancePink PowderOdorSlight odorColorPinkOdor ThresholdNot determined

Property Values
pH 9-9.5 (10% slurry in water)

Melting Point/Freezing Point>1300°CBoiling Point/Boiling RangeNoneFlash PointNone

Evaporation Rate None (Water = 1)

Flammability (Solid, Gas) None
Explosivity Not explosive

 Vapor Pressure
 None
 @68°F (20°C)

 Vapor Density
 > 1.0
 (Air=1)

Vapor Density > 1. Specific Gravity 2.8

Water Solubility <1mg/ml @ 21°C (RAD)

Solubility in other solvents

 Ethanol
 <1mg/ml @ 21°C (RAD)</th>

 Acetone
 <1mg/ml @ 21°C (RAD)</th>

Cold Acids Insoluble
Alkalies Insoluble

Decomposition Temperature 1652°-1832°F (900°-1000°C)

10. STABILITY AND REACTIVITY

Reactivity

Inert - Not reactive.

Chemical Stability

Chemically stable.

Possibility of Hazardous Reactions

No hazardous reaction.

Conditions to Avoid

None.

Incompatible Materials

None known.

Hazardous Decomposition Products

None.

11. TOXICOLOGICAL INFORMATION

Delayed and immediate effects as well as chronic effects from short and long-term exposure

NIOSH registry number: WW2710000

SAX toxicity evaluation: THR: Not available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

IARC: In 2006, IARC concluded that inhaled talc not containing asbestos or asbestiform fibers is not classified as a human

carcinogen (Group 3).

In 2006, IARC ruled that there is limited evidence that the use of talc-based body powder for perineal dusting is a possible risk factor for ovarian cancer (Group 2B). This is not a route of exposure relevant to workers and applies

only to one specific use of talc.

OSHA: Not lisited

ACGIH: A4-not classified as a human carcinogen

WHMIS: Class D-2A
NTP: Not listed

Tumorigenic Data

TCLo: ihl-rat 11 mg/m3/1Y-1
TDLo:: imp-rat 200 mg/kg

Other Toxicity Data: Skin and eye irritation data: skn-hmn 300 ug/3D-I MLD

Teratogenicity (reproductive effects data): Repeated ingestion of large doses of talc for 10 and 13 successive days by mice and

rabbits revealed negative teratogenic ans carcinogenic results.

Mutation Data: Not available

12. ECOLOGICAL INFORMATION

Ecotoxicity:

No data is available on this product. No specific adverse effects known.

<u>Persistence and Degradability:</u> No data is available on this product. Product is an inorganic substance and therefore is not

considered biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

US Department of Transportation (DOT):

Canadian Transportation of Dangerous Goods:

Land Transport – ADR/RID:

No classification assigned

Harmonized Tariff Code: Talc – crushed or powdered. 2526.20.00 (stat suffux 00)

EPA TSCA 12(B) Export Notification: Not listed

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean

Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Other Pertinent Classifications/Regulations:

California PROP 65 Status: Talc listed

State Right-To-Know: Talc listed in IL, MA, NJ, PA, FL

Clean Air Act – Ozone depleting chemicals (ODC): None CONEG Approved Packaging: Yes

16. REGULATORYINFORMATION

<u>NFPA</u>	Health Hazards 0	Flammability 0	Instability 0	Special Hazards Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	0	0	0	B- Safety Glasses,

Gloves

Issue Date:17-Sept-2008Revision Date:21-Apr-2022Revision Note:3-Year Update

Disclaimer

Information in the SDS is provided in good faith, but we assume no liability for its use or misuse. It is furnished without any warranty of merchantability or any other warranty, express or implied. We shall not be liable for any claims, losses or damages of any vendee or third party or for lost profits or any special, indirect, incidental, consequential of exemplary damages, however they arise. Users must make their own investigations to determine suitability.

End of Safety Data Sheet